



MULTIGROUT 600

General Purpose Unsanded Tile Grout for 1-3 mm Joints

Description:

MULTIGROUT 600 is a Polymer Modified general purpose unsanded tile grout available in various colours that enhance the aesthetics of wall and floor tiles.

MULTIGROUT 600 provide long service life in internal and external applications.

It can be applied vertically and horizontally at the joint width of 1-3mm.

Advantages:

MULTIGROUT 600 is available in variety of colours that provide a decorative, easy to clean, durable, stain free and non-discoloration surface.

MULTIGROUT 600 is suitable for all kind of internal and external surfaces with the ease in application.

MULTIGROUT 600 has very good adhesion with Ceramics, Porcelain, Vitrified Tiles, Marble, Granite, natural and artificial stones.

MULTIGROUT 600 is environmentally friendly and odorless material.

Uses:

MULTIGROUT 600 can be used for floor and wall surfaces like;

- Ceramics, Porcelain & Vitrified Tiles.
- Marble, Natural Stones & Granite.
- Mosaic & Pavers.
- Query Tiles & Terracotta Tiles.

MULTIGROUT 600 is suitable for Kitchen, Bathrooms, wet areas, balcony, drawing room, living rooms etc.

Application Method :

Surface must be sound, clean, and free from dirt, dust, and oil. Tile adhesive should be fully cured before application of MULTIGROUT 600.

Clean the joint properly and remove all tile adhesive residue and loose material. Sharp edge scraper or high-pressure jet water or air can be used to clean the joints. Ensure that there should not be any standing water in the joint before application of MULTIGROUT 600.

Mix 3 part MULTIGROUT 600 with 1 part clean water until a non-sag homogeneous mixture is prepared. Prepared paste should be free from pebbles/stones.

Apply MULTIGROUT 600 into the joint with the help of scraper / soft rubber / Soft PVC or Silicon trowel at 45o angle. Ensure that applied paste fills the completely and evenly.

Once material partially dry (after 5 - 6 hours), clean the edges of joint with the help of water and wet sponge or cloth.

Leave MULTIGROUT 600 to dry for 24 hours before open for light traffic and 5 days for full exposure.

Production Information

Chemical Based	Polymer Modified Cement
Primary Form	Fine Powder
Packaging	1 KG
Shelf Life	12 months
Storage Conditions	Store between 5°C to 35°C in dry place
Joint Width	1.0mm to 3.0mm
Pot Life	Upto 2 hours at 25°C
Light Traffic	After 24 Hours
Full Exposure	After 5 Days

Grout Consumptikom Sqm/Kg

Tile Size (Inches)	1mm Joint	2mm Joint	3mm Joint
8x12	5.00	2.50	1.50
10x16	6.50	3.00	2.00
10x20	7.00	3.50	2.50
8x26	6.50	3.00	2.00
6x37	5.50	3.00	2.00
9x36	7.50	4.00	2.50
12x12	6.50	3.00	2.00
12x18	7.50	4.00	2.50
12x24	8.50	4.00	3.00
16x16	8.50	4.00	3.00
16x32	9.00	4.50	3.00
24x24	10.00	5.00	3.50
24x48	13.50	6.50	4.50

Grout Color Chart

White		
Almond/Ivory		Saltillo
Marble Beige		Sandal Beige
Inner Gold		Canyon Red
Brown		Blood Red
Dark Brown		Sky Blue
Smoke Grey		Exotic Blue
Silver Grey		Mauve
Dark Grey		Sea Green
Black		Green
Sunrise		Sage





MULTIGROUT 600

General Purpose Unsanded Tile Grout for 1-3 mm Joints

Precautions:

Always use safety gloves, goggles, and safety shoes before start of application. For best results and good aesthetics, use soft rubber or silicon trowel for finishing of **MULTIGROUT 600**. Repack the **MULTIGROUT 600** pack to ensure the shelf life of leftover material. In case of eye contact, rinse with plenty of clean warm water. Seek medical assistance if necessary. Avoid application of **MULTIGROUT 600** if water is standing inside joints. The atmospheric temperature should be between 10°C to 35°C during application. Clean all tools and equipment instantly with water. Keep out of reach of children.

Limitations:

MULTIGROUT 600 is not chemical resistant. For application under aggressive condition, consult with MultiTech Chemicals Technical Team for advice. **MULTIGROUT 600** cannot be applied at joints subject to movement and expansion. **MULTIGROUT 600** is designed to fill the gap upto 3mm between tiles. For joints, having more than 3mm space, please consult with MultiTech Chemicals Technical Team for advice. Grout Consumption Chart is only for guidance. Actual consumption may vary according to the site conditions.

Disclaimer:

The information supplied in our literature or given by our employees is based upon extensive experience and together with that supplied by our agents or distributors, is given in good faith in order to help our customers. Our company policy is one of continuous research and development; we therefor reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products. However, as we have no control over site conditions or the execution of the work. We accept no liability for any loss or damage which may arise as a result thereof.

Health & Safety:

Always use appropriate PPE including gloves, goggles and a barrier cream to avoid contact with skin and eyes. Should contact with skin or eyes occur, wash immediately with plenty of clean water and seek medical advice. If swallowed, seek medical attention immediately. Do not induce vomiting. Avoid inhalation and ensure adequate ventilation or suitable respiratory equipment if working in confined spaces. Do not expose products to fire or naked flames under any circumstances.

